


Page 1 of 5 Print Date 20.05.2019	Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Oleum Cajeputi artificiale	 Revision Date 20.05.2019
--	--	---

1 Identification of the substance/mixture and of the company/undertaking

- Informations to product No. g662
- Product name:

Oleum Cajeputi artificiale Kajeputöl, naturidentisch Cajeput oil, nature identical

- Supplier of the Product / responsible Company:

Caesar & Loretz GmbH
 Herderstr. 31
 40721 Hilden
 Tel.: 02103/4994-0
 Fax: 02103/32360
 e-mail: info@caelo.de

- Emergency telephone:

Giftinformationszentrum Mainz
 Langenbeckstr. 1, 55131 Mainz
 Tel.: 06131/19240

2 Hazards identification

- GHS-Labeling Elements:



- Signal word: **Danger**


- H-Phrases:

H226 Flammable liquid and vapour
 H315 Causes skin irritation
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction
 H304 May be fatal if swallowed and enters airways
 H411 Toxic to aquatic life with long lasting effects

- P-Phrases:

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking
 P301 IF SWALLOWED:
 P310 Immediately call a POISON CENTER or doctor/physician
 P303 IF ON SKIN :
 P352 Wash with plenty of soap and water.
 P305 IF IN EYES:
 P351 Rinse cautiously with water for several minutes.

Flam. Liq. 3
Asp. Tox. 1
Aquatic Acute 2

<p>Page 2 of 5</p> <p>Print Date 20.05.2019</p>	<p>Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)</p> <p>Oleum Cajeputi artificiale</p>	 <p>Revision Date 20.05.2019</p>
---	---	---

Aquatic Chronic 2
Skin Irrit. 2
Eye Irrit. 2
Skin Sens. 1

2 Composition / information on ingredients

- **Chemical characterization:**
- CAS-No. Substance name**
 - Cajeput oil, nature identical
- **EINECS-No.:** -
- **REACH Reg. No.:** - (mixture)
- **INCI-Name:** -
- **Description:** Nature identical essential oil

Hazardous components:

CAS: 138-86-3, EINECS: 205-341-0, **Limonen**, H226; H304; H400; H410; H315; H317, 10-19,99%
CAS: 98-55-5, EINECS: 202-680-6, **p-Menth-1-en-8-ol**, H315; H319, 10-19,99%
CAS: 80-26-2, EINECS: 201-265-7, **p-Menth-1-en-8-ylacetat**, H411, 5-9,99%
CAS: 8000-41-7, EINECS: 232-268-1, **Terpineol**, H315; H319, 5-9,99%
CAS: 99-85-4, EINECS: 202-794-6, **p-Mentha-1,4-dien**, H226; H304, 2,5-5%
CAS: 99-87-6, EINECS: 202-796-7, **p-Cymol**, H226; H304; H411, 1-2,49%
CAS: 7785-26-4, EINECS: 232-077-3, **alpha-Pinen**, H226; H304; H400; H410; H317, 1-2,49%

4 First aid measures


- **after inhalation:** Fresh air. If irritation of respiratory ways continues, seek medical advice.
- **after skin contact:** Wash off with water, remove contaminated clothing.
- **after eye contact:** Rinse out with plenty of water with the eyelid wide open. If feeling unwell continuously seek medical advice.
- **after swallowing:** Seek medical advice immediately.

5 Fire-fighting measures

- **Suitable extinguishing media:** All regular extinguishing media can be used. Select fire fighting measures suitable to surrounding environment.
- **Specific hazards during fire fighting:** Combustible
- **Special protective equipment for fire-fighters:** Do not inhale combustion gases. Wear respiratory protection.
- **Additional information:** Prevent fire extinguishing water from contaminating surface water, the ground water system or soil. Residues must be deposited according to local regulations.

6 Accidental release measures

- **Personal protective measures:** Avoid contact with substance, Wear protective equipment. Good ventilation of working place.
- **Environmental protective measures:** Prevent from entering into drains. If product is entering drainage ditch or surface waters inform responsible authorities.
- **Methods for cleaning:** Absorb with liquid-binding material: Sand, silica gel, acid binder, universal binder, saw dust, disposal of contaminated material see chapter 13. Good ventilation of working place.

<p>Page 3 of 5</p> <p>Print Date 20.05.2019</p>	<p>Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)</p> <p>Oleum Cajeputi artificiale</p>	 <p>Revision Date 20.05.2019</p>
---	---	---

7 Handling and storage

- **Handling:** Good ventilation / exhaustion of working place. Avoid formation of aerosols.
- **Informations to fire or explosion protection:** Good ventilation / exhaustion of working place and storage place. Keep away from ignition sources – Do not smoke.
- **Storage:**
- **Requirements for storage areas and containers:**
Tightly closed. Store at a dry place. At room temperature (+15°C to +25°C). Store at a good ventilated place. Avoid safely penetration into soil.
- **Advices on common storage:** Not required.
- **Additional informations to storage conditions:** none

8 Exposure controls / personal protective equipment


- **Components with limit values that require monitoring at the workplace:** The product does not contain relevant quantities of substances with limit values that require monitoring at the workplace.
- **Personal protective equipment:**
- **General protective and hygiene measures:** The usual precaution measures during handling of chemicals are to observe.
- **Respiratory protection:** Only required if aerosols or vapours are generated.
- **Hand protection:** Protection gloves of rubber or latex or PVZ, for full contact 15 minutes maximum: Neopren. Suitable gloves for enduring contact, Material: Nitrile rubber/Nitrile latex Penetration time > 480 min., Thickness: 0,35 mm.
- **Eye protection:** Safety glasses

9 Physical and chemical properties

- **Form:** liquid
- **Colour:** colourless
- **Odour:** strong aromatic.
- **Melting point / melting range:** not determined
- **Boiling point / boiling range:** not determined
- **Flash point:** 57 °C
- **Density:** (20 °C) 0,91 g/cm³
- **Solubility in / Miscibility with**
- **Water:** not soluble

10 Stability and reactivity

- **Thermal decomposition / conditions to avoid:**
No decomposition during appropriate use.
- **Materials to avoid:** Strong oxidizers, strong acids and bases.
- **Hazardous reactions:** No hazardous reactions known.
- **Hazardous decomposition products:** none

<p>Page 4 of 5</p> <p>Print Date 20.05.2019</p>	<p>Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)</p> <p>Oleum Cajeputi artificiale</p>	 <p>Revision Date 20.05.2019</p>
---	---	---

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on skin:** Irritant effect on skin and mucous membranes.
- **on eyes:** Slight irritant effect.
- **Sensitization:** Sensitization by skin contact possible.

12 Ecological information

- **Ecotoxicological effects:**
Toxic for fishes.
- **General advices:** Do not allow product to reach ground water, water course or sewage system even in small quantities. Danger to drinking water if even small quantities leak into the ground. In environmental waters toxic for fishes and plankton, Toxic for water organisms.
- **Water hazard class:** 2 (self classification): hazardous for water.

13 Disposal considerations


- **Product:**
- **Recommendation:** Disposal according to local regulations as pharmaceutical waste.
- **Empty contaminated packaging:**
- **Recommendation:** Disposal according to the local regulations.

14 Transport informations

- **Land transport according to ADR:**
- **Proper shipping name:** Flammable liquids, n.o.s., Essential oil.
- **Class:** 3
- **UN-number:** 1993
- **Packing group:** III
- **Classification code:** F1
- **Limited quantities (Table 3.4.6. ADR):** 5 Liter
- **Hazard classification number:** 30
- **Special provisions (Chapter 3.3 ADR):** 274, 640E
- **Additional informations for sea transport IMDG:**
- **EMS-No.:** F-E, S-E
- **Properties:** Fp=57°C

15 Regulatory information

- **Labelling according to actual legislation (GHS, Globally Harmonized System of Classification and Labelling of Chemicals):**
The product is classified and labelled according to GHS-regulations.
- **Hazard symbols:** GHS02, GHS07, GHS08, GHS09
- **Signal word:** Danger

Page 5 of 5 Print Date 20.05.2019	Material Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Oleum Cajeputi artificiale	 Revision Date 20.05.2019
--	--	---

• **H-Phrases:**

H226 Flammable liquid and vapour

H315 Causes skin irritation

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction

H304 May be fatal if swallowed and enters airways

H411 Toxic to aquatic life with long lasting effects

• **P-Phrases:**

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking

P301 IF SWALLOWED:

P310 Immediately call a POISON CENTER or doctor/physician

P303 IF ON SKIN :

P352 Wash with plenty of soap and water.

P305 IF IN EYES:

P351 Rinse cautiously with water for several minutes.

• **National regulations (Germany):**

• **Water hazard class:** see chapter 12

• **Storage class TRGS 510:** 3

• **VbF class:** AIII

16 Other Information

The information provided in this MSDS is correct to the best of our knowledge at the date of edition.

• **Reason for last revision:** Adjustment to regulation (EC) 1907/2006 (REACH) and GHS-labelling system.